

## **LEISURESALES** **INSTALLATION REQUIRMENTS**

### **CLASSIC TAN E-lite (the Equipment)**

**Electrical Requirements. Please issue this sheet to your electrical contractor.**

**IMPORTANT: THE MAIN SUPPLY MUST MEET THE REQUIREMENTS OF THE IEE WIRING REGULATIONS. A COMPETENT PERSON MUST INSTALL THIS UNIT. IT IS OBLIGATORY FOR YOU TO OBTAIN A CERTIFICATE TO VERIFY THIS, OTHERWISE THE EQUIPMENT CANNOT BE CONNECTED TO THE MAINS SUPPLY.**

MAIN SUPPLY: 240v 50hz single phase. **THE EQUIPMENT MUST BE EARTHED**

**MINIMUM FUSE RATING: 2** AMPS

**IMPORTANT:** A suitable **surface mounted** isolator or switched socket must be installed near to the Equipment, to allow maintenance. This must be sited to prevent any trailing cables and mounted at least one metre from floor level.

**MINIMUM RECOMMENDED ROOM SIZE 2380 X 1700 x 2500**

### **INSTALLATION**

The Equipment is completely self-contained, so does not require plumbing to a water supply or drainage system. The Equipment is self-cleaning and maintains the clarity of its spray nozzles by running a cleaning cycle after every session. Containers are provided for water and waste. If preferred the Equipment can be connected directly to a water supply and an external drain.

### **FLOORING REQUIREMENT**

A water impervious floor is required

### **Drainage requirement**

DRAIN HOSE DIAMETER 10mm

WATER HOSE DIAMETER 10mm

### **TIMER CONTROL**

The Equipment contains an electronic control with session counter, this **must** be used in conjunction with an external electronic timer (i.e. a token meter), computer management system or a manually operated pushbutton. Whichever system is used, it must provide a momentary pulse of about one second.

If in doubt please contact our technical department.

Detailed technical help is available from our technical department, including room plans; they are able to produce CAD drawings to help in optimising your studio layout.

For further assistance Telephone 01625 501611 or Fax 01625 502833